



stride80® Purpose-built to ignite growth!

Accu-Time Systems' new stride80® was built to ignite growth. Whether you are leveraging the stride80 to easily and seamlessly integrate an existing Android application or developing new and interactive employee self-service applications, the stride80 brings a new competitive edge to your business; opening the door to new markets.

With our comprehensive Software Development Kit (SDK) to guide you, you'll be able to quickly deploy your most innovative employee self-service applications; and if you ever need it, our customer support team is here to provide expert support.

stride80® features include:

- Android-based
- 8" Widescreen Touch Display
- Speakers
- Microphone
- eMMC – 16GB Storage

To learn more about ATS and stride80,
visit www.accu-time.com or
call -1 860.870.5000



stride80® Terminal Specifications

Operating System

- Android OS
- Software Development Kit available

User Interface

- 8" Capacitive multi-touch color screen
- Software controllable multicolor LED indicator bar
- Microphone and speaker
- Presence sensor
- LED indicator for camera usage
- **Optional** - - 8 Mega Pixel Camera - Supports photo and video
- **Optional** - - Keypad - 20 keys 0-9 , F1-F6, Clear and Enter keys

Memory

- 2GB

Mass Storage

- 16GB of which 5GB are user available

Central Processing Unit (CPU)

- Quad Core A7, 1.1GHz

Communications

- 10/100 Mbps, Ethernet with DHCP, Static IP address
- Optional - 4G GSM Modem
- WIFI - 2.4Gbit/s, 802.11 b/g/n

Dimensions

- **Base Model:**
 - » 8.98" wide x 7.69" high x 3.13" deep
 - » 228.2mm wide x 195.3mm high x 79.6mm deep
- **XL Model:**
 - » 12.17" wide x 7.69" high x 3.13" deep
 - » 309.0mm wide x 195.3mm high x 79.6mm deep
- **Mag swipe add on**
 - » 1.16" x 3.74" x 1.34"
 - » 29.47mm x 96mm x 34.04mm

Power

- 12V DC 30W output | Terminal power consumption less than 30 Watts
- **Optional** - PoE IEEE 802.3at (30W, PoE+)
- **Optional** - - Battery - Li-ion | 8.4v @ 2600 mAh up to 1 hr of operation.

Environment

- Operating Temperature: 0° to 50°C (32° to 122°F)

Supported readers and card technologies

- **Optional** - Barcode scanner Visible red light
- **Optional** - Biometric readers
 - » Lumidigm 1:N 1,300 & 1:1 50,000 templates
 - » Suprema USB capacitive & optical
 - » 1:N 5000 & 1:1 50,000 templates
- **Optional** - Proximity readers - HID Prox, iClass SE, Fare and Marin
- **Optional** - Mag stripe reader - Track 1, 2, 3

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters

20-B International Drive

Windsor, CT 06095

TEL: (860) 870-5000

FAX: (860) 872-1511

Toll Free: (800) 355-4648

sales@accu-time.com

www.accu-time.com

EMEA & APAC

United Kingdom

TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599



TRACY

For more information:
www.tracyinc.com
(866) 356-0663